



PCT/GB 2003 / 0 0 4 9 3 6



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

RECEIVED

03 FEB 2004

WIPO

PCT

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, L.C. or PLC.


Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed *Andrew Gersey*

Dated 4 December 2003

**Best Available Copy**

Patent 1977  
(Rule 16)



14NOV02 0263369-3 002818  
P01/7700 0.00-026528.8

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

- Your reference  
A10617GB-DJL
- Patent application number  
(The Patent Office will fill in this part)  
0226528.8 14 NOV 2002
- Full name, address and postcode of the or of each applicant (underline all surnames)  
J.C.Bamford Excavators Limited  
Rocester  
Uttoxeter  
Staffordshire  
ST14 5JP  
Patents ADP number (if you know it)  
4290359001  
If the applicant is a corporate body, give the country/state of its incorporation  
United Kingdom
- Title of the invention  
Excavating and Loading Machine
- Name of your agent (if you have one)  
Forrester Ketley & Co.  
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)  
Chamberlain House  
Paradise Place  
Birmingham  
B3 3HP  
Patents ADP number (if you know it)  
133005
- If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number  

Country	Priority application number (if you know it)	Date of filing (day / month / year)
---------	--	-------------------------------------
- If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application  

Number of earlier application	Date of filing (day / month / year)
-------------------------------	-------------------------------------
- Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:  
a) any applicant named in part 3 is not an inventor, or  
b) there is an inventor who is not named as an applicant, or  
c) any named applicant is a corporate body.  
See note (d))  
Yes

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	8
Claim(s)	3
Abstract	1
Drawing(s)	3

PM  
tg

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) Yes

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature  
Forrester Ketley & Co.

Date  
13 November, 2002

12. Name and daytime telephone number of person to contact in the United Kingdom  
David J Lucking  
0121 236 0484

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

PATENTS ACT 1977

A10617GB/DJL

Title: Excavating and Loading Machine

Description of Invention

This invention relates to a wheeled excavating and loading machine.

Excavating and loading machines are known which have a body with a loading arm at a front end of the body and an excavating arm at a rear of the body, and a wheeled ground engaging structure, such as a pair of axles carrying ground engaging wheels.

Such machines are either steerable by the wheels on one or both of the axles being steerable, or by the body being articulated.

In each case, a combined excavating and loading machine provides for an owner, a versatile machine which is capable of performing a variety of excavating and loading operations. However, in providing a machine which is capable of performing both excavating and loading operations, design compromises have been made with the result that when the machine is performing particularly excavating operations, machines have tended not to be as capable as a dedicated excavating machine for example of the kind in which an excavating arm is carried on a superstructure which is rotatable about a generally upright axis, on a ground engaging structure.

This is particularly the case where configurations of the body and wheeled ground engaging structure of the combined excavating and loading machine can prevent a trench readily being excavated closely adjacent an obstacle such as a wall. On some combined machines the, usually centrally mounted, excavating arm can be moved sideways on a carriage so that the arm may be used to excavate a trench closer to the obstacle, but moving the arm in this manner can present visibility difficulties for an operator.

According to a first aspect of the invention we provide an excavating and loading machine having a body with a front end and a rear end, the body being carried on a steerable wheeled ground engaging structure, the machine including a loading arm assembly which is mounted on the body and extends forwardly of the body, and an excavating arm, and wherein the excavating arm is mounted on a superstructure which includes an operator's cab, the superstructure being rotatable about a generally upright axis relative to the body during the performance of excavating operations.

Thus a machine in accordance with the invention extends the capabilities of known excavating and loading machines, in that the excavating arm is movable together with the cab to enable excavating operations to be carried out in a wide variety of positions, without having to move the excavating arm along a carriage to a position where the operator may be unsighted. Thus the advantages of dedicated excavating machines of the kind mentioned above, are realised in a combined excavating and loading machine.

In a preferred arrangement, the superstructure is mounted at or towards a rear of the body, e.g. over a rear axle of the wheeled ground engaging structure, in which case the rotatable superstructure may carry mudguards for the rear wheels. Although these will rotate with the superstructure, when the machine is driven over the ground, the superstructure will be orientated in a straight ahead position, with the excavating arm mounting generally centrally of the body between the sides.

Thus the cab may include within, first controls for driving the machine over the ground and for operating the loading arm assembly, which the operator will use when the cab is in the straight ahead position, and second controls for operating the excavating arm and for rotating the superstructure. The cab may include a rotatable operator's seat to enable the driver to access and use the first or second controls as appropriate.

The loading arm assembly may be of the single arm kind, the single arm being mounted in a generally central position between sides of the body, forwardly of the superstructure.

In a preferred arrangement, the loading arm assembly includes a pair of loader arms each extending along a side of the body.

In any event it will be realised that the rotatable superstructure will be incapable of a full  $360^\circ$  rotation without the excavating arm fouling the body and/or the loading arm assembly, but preferably stops are provided mechanically to limit the rotation of the superstructure although the superstructure may rotate through up to  $300^\circ$ .

Additionally, preferably the excavating arm is mounted on the superstructure by a mounting which permits the arm to slew relative to the superstructure, about a generally upright slew axis for added versatility, as well as to permit the excavating arm to be raised and lowered about a generally horizontal axis. The excavating arm may be of the kind including at least two sections which are relatively moveable about a generally horizontal axis, with there being an excavating tool, such as an excavating bucket, mounted at an outer end of the excavating arm, although other tools including non-excavating tools may be mounted on the excavating arm for performing specialised work operations.

The body of the machine may house an engine to power the machine, the engine being provided preferably forwardly of the rotatable superstructure, generally centrally between the sides of the body. Where the loading arm assembly has a single arm, the engine may be positioned beneath an inner end of the loading arm, or where the loading arm assembly includes a pair of arms, the engine may be provided between the arms, at least when in a lowered condition. Alternatively the engine may be mounted to one side of the machine.

The loading arm assembly may be pivotal relative to the body about a generally horizontal mounting axis, and may include a plurality of telescopic sections whether a single arm or double arm, a loading tool, such as a bucket may be mounted at an outermost end of the loading arm assembly.

The superstructure may be rotatable relative to the body by a hydraulic or electric motor as desired.

Embodiments of the invention will now be described with reference to the accompanying drawings in which:-

FIGURE 1 is an illustrative perspective view of an embodiment of the invention with a superstructure in one rotational position;

FIGURE 2 is an illustrative rear view of the machine of figure 1 with the superstructure in an alternative rotational position, but with stabiliser arms omitted for clarity.

FIGURE 3 is a view similar to figure 1, but showing an alternative embodiment of the invention.

Referring to figures 1 and 2 of the drawings there is shown an excavating and loading machine 10 which includes a body 11 carried on a wheeled ground engaging structure 12 which includes a front axle 13 and a rear axle 14, wheels 15 carried by the front axle 13 being steerable by hydraulic and/or mechanical means.

Rear wheels 16 carried by the rear axle 14 are not steerable in this example, but in another embodiment, may be, and/or the body 11 may be articulated.

Mounted on the body 11 at a mounting 18 is a loading arm assembly 20 which includes a single arm which extends forwardly of the mounting 18 beyond a front end of the machine 10. The mounting 18 permits the loading arm assembly 20 to be raised and lowered about a generally horizontal axis A, by hydraulic or other actuators 21.

The mounting 18 for the loading arm assembly 20 is generally central of the body 11 between sides of the body 11, and the loading arm assembly 20 extends downwardly over a bonnet 22 beneath which an engine (not shown) is housed. Thus in this example the engine is generally centrally mounted towards the front of the body 11.

The loading arm assembly 20 in this example includes two telescopic sections 20a, and 20b, with there being a loading bucket 23 or other loading tool at the outermost end of the loading arm assembly 20, but the loading arm assembly 20 may have more than two such telescopic sections if desired.

Mounted on the body 11 is a superstructure 25 which includes an operator's cab 26. The operator's cab 26 includes within it, a rotatable operator's seat 27 which may be rotated to enable an operator to access and operate first controls, for driving the machine 10 over the ground and for operating the loading arm assembly 20, or to enable the operator to access second controls within the cab 26.

The superstructure 25 is mounted towards a rear end of the body 11 for rotation about a generally upright axis B which is located generally centrally of the body 11 between the sides by a hydraulic or electrically powered motor, controlled by the second controls within the cab 26. Moreover the superstructure 25 has mounted upon it, an excavating arm 30 the operation of which is also controlled by the second controls within the cab 26.

The excavating arm 30 is mounted by a mounting 32 generally centrally of the sides of the cab 26, for movement about a further generally upright axis C, e.g. on a king post or the like, and for movement about a generally horizontal axis D, such movements being effected by respective hydraulic actuators or the like controlled by the second controls within the cab 26. A king post type of mounting typically would permit the excavating arm 30 to slew through up to 180°.



The excavating arm 30 has two sections 30a, 30b in this example which are relatively pivotal about a horizontal axis indicated at E, again by actuators controlled by the second controls in the cab 26, and at the extreme outward end of the arm 30 there is mounted an excavating tool 35, i.e. a bucket in this example, although the bucket 35 may be replaced by another tool, such as a hammering tool for specialised work operations. Again the bucket 35 is controlled by the second controls in the cab 26.

Because of the position of the mounting 18 for the loading arm 20 and other body 11 features, the superstructure 25 cannot be rotated or slewed on the body 11 though a full 360°, but preferably can be rotated or slewed through up to 300°, when mechanical stops provided on a slewing ring will engage to prevent the superstructure 25 being rotated such that damage might be caused to the body 11. Instead of or in addition to mechanical stops, hydraulic interlocks might be provided to restrict rotation of the superstructure 25 beyond its design limit, e.g. a hydraulic brake may be provided for a hydraulic motor used to slew the superstructure 25.

When it is desired to use the machine 10 to perform loading operations, the superstructure 25 is rotated so that the excavating arm 30 mounting 32 is located at the rear of the machine 10 generally centrally between the sides of the body 11. The superstructure 25 is locked in this position, preferably mechanically and the operator's seat 27 would be orientated so as to face forward. Thus the operator would operate the first controls, and loading operations may be performed. Mudguards 42 carried on the superstructure 25 would, with the superstructure 25 in this position, be above the rear wheels 16 so that these may perform their function of reducing spraying of mud as the machine 10 is moved over the ground.

When it is desired to perform excavating operations, and mechanical superstructure locks are released, and the operator's seat 27 is rotated in the cab 26 to enable the operator to access and use the second controls. Thus the

operator may rotate the superstructure 25 and operate the excavating arm 30 whilst performing an excavating operation.

As indicated in figure 1, an excavating operation, e.g. to dig a trench alongside an obstacle may be carried out by combining rotating the superstructure 25 and slewing the excavating arm 30 about the upright slewing axis C.

Further features of the machine 10 will be apparent to those skilled in the art from the drawings. For example, a pair of stabiliser legs 50, 51 may be provided at the rear of the body 11 (only shown in figure 1), to stabilise the machine 10 during excavating operations, the legs 50, 51 being lowerable into engagement with the ground, and raisable out of contact with the ground mechanically or by suitable power means such as hydraulic actuators.

It can be seen that the superstructure 25 is positioned above the rear wheels 16 of the machine 10 in this example, for further stability and the mounting 32 for the excavating arm 30 on the superstructure may, when the superstructure is adequately rotated, be above the rear wheels 16.

In figure 3, a machine 10 similar to that shown in figures 1 and 2 is shown, but in this example, the loading arm assembly 20, instead of having a single arm, has a pair of arms 20c. When the assembly 10 is lowered, the arms 20c extend either side of the body 11 with the bonnet 22 and the engine beneath the bonnet, between them. Otherwise similar parts to the machine 10 of figure 1 are indicated by the same references.

If desired, for a machine 10 of the kind shown in figures 1 or 3, instead of the machine engine being provided generally centrally of the body 10 beneath the bonnet 22, a side mounted engine may be provided.

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any

combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. An excavating and loading machine having a body with a front end and a rear end, the body being carried on a steerable wheeled ground engaging structure, the machine including a loading arm assembly which is mounted on the body and extends forwardly of the body, and an excavating arm, and wherein the excavating arm is mounted on a superstructure which includes an operator's cab, the superstructure being rotatable about a generally upright axis relative to the body during the performance of excavating operations.
2. A machine according to claim 1 wherein the superstructure is mounted at or towards a rear of the body.
3. A machine according to claim 2 wherein the superstructure is mounted over a rear axle of the wheeled ground engaging structure and the rotatable superstructure carries mudguards for the rear wheels.
4. A machine according to any one of the preceding claims wherein the cab includes within it, first controls for driving the machine over the ground and for operating the loading arm assembly, and second controls for operating the excavating arm and for rotating the superstructure, and a rotatable operator's seat to enable the driver to access and use the first or second controls.
5. A machine according to any one of the preceding claims wherein the loading arm assembly is mounted in a generally central position between sides of the body, forwardly of the superstructure.

6. A machine according to any one of claims 1 to 4 wherein the loading arm assembly includes a pair of loader arms each extending along a side of the body.
7. A machine according to any one of the preceding claims wherein the rotatable superstructure is capable of less than a full 360° rotation, with there being stops mechanically to limit the rotation of the superstructure.
8. A machine according to claim 7 wherein the superstructure is rotatable though up to 300°.
9. A machine according to any one of the preceding claims wherein the excavating arm is mounted on the superstructure by a mounting which permits the arm to slew relative to the superstructure, about a generally upright slew axis as well as to permit the excavating arm to be raised and lowered about a generally horizontal axis.
10. A machine according to claim 8 wherein the excavating arm is of the kind including at least two sections which are relatively moveable about a generally horizontal axis, with there being an excavating tool mounted at an outer end of the excavating arm.
11. A machine according to any one of the preceding claims wherein the body of the machine houses an engine to power the machine, the engine being provided forwardly of the rotatable superstructure, generally centrally between the sides of the body.
12. A machine according to claim 11 where appended to claim 5 wherein the engine is mounted beneath an inner end of the loading arm.

13. A machine according to claim 11 where appended to claim 6 wherein the engine is provided between the arms.
14. A machine according to any one of the preceding claims wherein the loading arm assembly is pivotal relative to the body about a generally horizontal mounting axis.
15. A machine according to any one of the preceding claims wherein the loading arm assembly includes a plurality of telescopic sections, with a loading tool mounted at an outermost end of the loading arm.
16. A machine according to any one of the preceding claims wherein the superstructure is rotatable relative to the body by a hydraulic or electric motor.
17. An excavating and loading machine substantially as hereinbefore described with reference to and/or as shown in the accompanying drawings.
18. Any novel feature or novel combination of features described herein and/or as shown in the accompanying drawings.

## ABSTRACT

Title: Excavating and Loading Machine

An excavating and loading machine (10) has a body (11) with a front end and a rear end, the body (11) being carried on a steerable wheeled ground engaging structure, the machine (10) including a loading arm assembly (20) which is mounted on the body (11) and extends forwardly of the body (11), and an excavating arm (30), and wherein the excavating arm (30) is mounted on a superstructure (25) which includes an operator's cab (26), the superstructure (25) being rotatable about a generally upright axis (B) relative to the body (11) during the performance of excavating operations




FIG 1







FIG 2



**FIG 3**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**